

(12)

# **EUROPEAN PATENT APPLICATION**

(43) Date of publication: 16,07,1997 Bulletin 1997/29 (51) Int. CL<sup>6</sup>: G06T 11/00

(11)

(21) Application number: 96309578.1

(22) Date of filling: 31.12.1996

(84) Designated Contracting States: DE FR GB


(30) Profily: 11.01.1996 US 585030

(71) Applicant: XEROX CORPORATION Rochester New York 14644 (US) (72) Inventor: Venable, Dennis L. Marion, New York 14505 (US)

(74) Representative: Reynolds, Julian David et al Rank Xerox Ltd Patent Department Parkway Marlow Buckinghamshire SL7 1YL (GB)

# (54) System and method for synthesizing background texture

(57) A method backfills areas of an image with synthesized textures. This is realized by selecting a texture exemplar from an image and identifying an area of the image to be backfilled. An estimate of the synthesized texture is generated and predetermined spatial domain. constraints are applied to the estimate. The spatially constrained estimate is operated upon by a Fourier transform to create a spectral function. Predetermined spectral domain constraints are applied to the spectral function and an an inverse Fourier transform is performed thereon to produce a synthesized texture. The synthesized texture is inserted into the area of the image to be bacidilled if it is determined to be adequate. If the synthesized texture is inadequate, the synthesized texture is our through the synthesis process again until the the texture is adequate for backfilling



EP 0 784 293 A2

### Description

The present invention is directed to a system or method for synthesizing background texture in an image. More specrizely, the prosent invention is directed to a system or method which enables the reclaserant of unwarred objects or regions in an image with a synthesized background texture such that the edges bordering the deleted region are synonic.

In a production printing environment, the preparation of images for printing requires the removal of unwanted objects or regions in the image. For example, an image may contain a ball fying in a grassy yard wherein the ball is undesirable. Conventionally, to remove the unwanted object or region from the image, a region of the grassy yard withto out the ball would be electronically copied and pasted over the ball. This process is commonly known as cloning.

Although doning provides a way of removing unwanted objects or regions from the image, this process tends to produce images with have border ratifiants between the original background and the newly pasted over background, in other words, utilizing the conventional method of cloring to remove unwanted objects from an image, the resulting image may have artifacts which can facilitate the disction of the manipulation process as well as take away from the sethedes of the image. Therefore, it is desirable to provide a process which is capable of removing the unwanted objects while minimizing the border artifacts between the original background and the background image used to replace the unwanted objects.

One aspect of the present invention is a method for generating a synthesized feature. This method selects a texture extrmolar from an image and identifies an erea of the intege to be backfilled. Thereafts, the method generates an initial selection of the synthesized studyer, applies prodetermined spatial domain constraints to the initial estimate, priorities a Fourier transformation on the spatially constrained estimate, applies predetermined spatial domain constraints to the transformed sectivate, and performs an inverse Fourier transformation upon the spectrally constrained estimate to produce a synthesized texture.

Another aspect of the present invention is a method of backfilling areas of an image with synthesized features. This emethod comprises the abrementioned method, and the additional step of insenting the synthesized texture into the area of the image to be backfilled.

Preferably, substant (c2) normatizes the estimate of the synthesized texture by calculating a zero mean average of the bixel values in the estimate.

Atternatively, substep (c2) normalizes the estimate of the synthesized texture by calculating a mean average of the spiral values in the estimate, preterably by further dividing the mean averaged data by a determined standard deviation. Atternatively, substep (c2) normalizes the estimate of the synthesized texture by fitting a surface to the pixel values in the assimate to generate a polynomial representing the surfaced subtracting values generated by the polynomial representation.

resenting the surface from the pixel values. The invention further provides a programmable image processing apparatus when suitably programmed for carryus ing out the method of any of the appareded claims or according to any of the particular embodiments described herein, the apparatus including a processor, memory, and input/output forcularly.

Embodiments of the invention will now be described, by way of example, with reference to the accompanying drawinos, in which:

- 40 Figure 1 is a flowchart illustrating the synthesizing process of the present invention;
  - Figure 2 is a graphical representation illustrating non-normalized image data;
  - Figure 3 is a graphical representation illustrating normalized image data;
  - Figure 4 illustrates an image to be backfilled according to the concepts of the present invention;
  - Figure 5 illustrates a display window showing an image with an area to be removed:
  - Figure 6 illustrates a display window showing an area having the to be removed area in Figure 5;
    - Figure 7 illustrates a display window showing the removal of the object within the area illustrated in Figure 5;
    - Figure 8 illustrates the object removed from Figure 7;

45

- Figure 9 disstrates a display window showing an image with a selected texture exemplar;
- Figure 10 illustrates a display window showing the selected texture exemplar of Figure 9; and
- Figure 11 illustrates a processed image containing synthesized background texture generated according to the concepts of the present invention.

In the crawings, and in the description below, like reference numerals are used through to designate identical or equivalent elements or steps.

Figure 1 illustrates a flowchart showing the feature synthesis process according to one embodiment of the present invention. As illustrated in Figure 1, step S1 selects a texture exemplar. As noted above, the purpose of the present invention is to backfill areas of the image with synthesized textures that appear reasonable with respect to the surrounding areas. To meet this goal, the present invention interactively selects neighboring regions of the image which have textures similar to what is to be used as backfill. These selected regions are known as facture exemples.

The selected exemplar region is normalized using any conventional normalization process. (The preferred normalization processes will be described below). Then, the average Fourier transfer modulus of the normalized exemplar, representing the probability density of spatial frequencies, is calculated and used as spectral domain constraints in a later performed operation which will be discussed in more detail below.

After corrulating step S1, the present invention proceeds to step S3 where the image area to be synthesized is identified. In other words, a region of the image containing the area to be synthesized is selected. This region includes pixels that are part of the background and pixels that are part of the area to be deleted. The background pixels of this region are used to apply the spatial domain constraints in a later described operation. The actual area within this region to be synthesized is identified by ensing the pixel associated with the area.

At step SS, an initial estimate of the synthesized area is created. In the preferred embodiment of the present invention, he entire selected synthesized area is normalized with the pixels associated with the actual area to be synthesized the deleted area to being filled with zeros.

At step S7, the initial estimate created at step S5 has spatial domain constraints applied thereto. In the preferred embodiment of the present invention, the nontarget pokes of the selected image area are copied into the synthesized reach so as to provide a constraint which restains the confluintly of the known background pixels.

After the spatial domain constraints are applied to the identified area to be synthesized, the present invention performs a Fourier transformation at step S9 to yield a spectral function. Subsequently, spectral domain constraints are applied at step S11 to the spectral function. In the preferred embodiment of the present invention, the spectral domain constraints are applied by copying the average modulus of the exemplars as calculated in step S1 into the spectral function yielding a new function. The spectral domain constraints forces the synthesized area to maintain the spectral charactivistics of the asymptain region. Thereby retaining the correct factors.

Once the spectral domain constraints have been applied, the present invention performs an inverse Fourier transformation on the new function yielding a new estimate of the synthesized region. It is noted that the execution of steps 57, 59, 511, and 513 provide a process which reduces the entires at the border of the exacet and background pixels.

25

At sec S15, the new estimate of the synthesized region is analyzed to determine whether this estimate is adequate. If the estimate is adequate, it is solved to see that the estimate is adequate, it is solved to the second region with this synthesized to region with this synthesized toxture. However, if step S15 determines that the new estimate of the synthesized region is not adequate, the present invention performs steps S7. S9, S11, and S13 again to generate a new synthesized region. Thus, the present invention provides an iterative process to generate or create synthesized texture generated at step S13 is utilized as the estimate when resentain the the return process at step S1.

Figure 2 Illustrates a graphical representation of non-normalized image data A. To normalize this image data A. a normalization process is used to remove large scale intensity variations within local areas of the image white retaining the texture, or fine scale intensity variations, by reducing local areas to a zero mean intensity. One such normalization process is referred to as surface normalization which is uffilized in the preferred archodiment of the present invention.

Once the coefficients have been evaluated using least squares, an image pixel is normalized by subtracting the value of the polynomial at this port. Each pixel is processed accordingly to generate a region of normalized data. A representation of this process is illustrated in Figure 2 wherein A represents the image intensity and E prepresents the polynomial used to fit a surface to the image intensity. The result of this normalization is illustrated as curve C in Figure 3. As illustrated in Figure 3, surface normalization allows the removal of a fairly complicated intensity gradient from local area regions yelding a zero means intensity image.

Other types of normalization processes can also be utilized in connection with the present invention. For example, a zero mean normalization process wherein all the pixel values of an image are added and the average value is obtained. In this normalization process, the average value is then subtracted from the image intensity of each pixel reautino in an image with a zero mean value.

A Third normalization process which is applicable to the present invention is a Z normalization process. In this norormalization process, at the price values of an image are added and the average value is obtained. The average value is 
then subtracted from the image and the resultant from this subtraction is then divided by a standard deviation. Again, 
this results in an image with a zero mean value.

Thus, any normalization process can be utilized with the present invention so long as the normalization process is capable of removing large scale intensity variations within local areas of the image white retaining the texture, or fine scale intensity variations and white reducing local areas to a zero mean intensity. The noramifization process may include any of the processes described above or a combination thereof in a cascading arrangement.

As generally described above with respect to Figure 1, the synthesis process of the present invention is based on restoration by generalized projections; specifically, restoration from magnitude (RFM). Given an image containing a mall repide 7 to be replaced with a synthesized texture matching the surrounding texture, the process defines a rec-

tangular subset of the image 3 large enough to fully enclose region 9 and also include a significant number of pixels of background feature. Next, the process defines \$\frac{3}{2}\$ to be the region of \$\frac{3}{2}\$ not including \$\frac{3}{2}\$ and defines one or more rectangular regions \$\frac{2}{2}\$, or the same size as \$\frac{3}{2}\$ which contain only texture patterns similar to the pattern to be synthesized. The regions \$\frac{2}{2}\$ are known as exemptar regions.

The process then calculates  $M(\omega)$  which is the average modulus of the Fourier transform of an exemplar region E,  $M(\omega)$  represents the probability density of spatial frequencies in the desired background texture. Furthermore, to lactifie the discussion, let  $\Im(x,y)$  define the image intensity pattern of region  $\Im$ ; similarly for  $\Re(x,y)$  and let  $g_{\lambda}(x,y)$  be the  $k^{\alpha}$  strated of  $\Im(x,y)$  including the synthesized texture over  $\Re$ .

The synthesis process applies spatial and spectral constraints iteratively on the image data of region 5 until a result of acceptable quality is achieved. Acceptable quality, in the preferred embodiment of the present invention, is determined by the operator.

The spatial constraint is used to retain known background pixels, i.e., pixels that are elements of <u>B</u> retain their original value, whereas the special constraint is used to force the modulus of the synthesis to be M(e), the average modulus of the exemplair region. The application of these constraints is defined by projection operations onto sets of functions.

The two sets of functions involved in the synthesis of the present invention are: the set of functions  $\xi_2$  limited in space to region 3. with pixel values given by  $\mathfrak{A}$  (xy) over region  $\mathfrak{A}$ , and the set of all functions  $\xi_2$  which have a Fourier transform magnitude equal to the average exempler modulus  $M(\omega)$ . Thus,

$$52^{\infty} \{g(x) : g(x) = \underline{R}(x) \text{ for } x \in \underline{R}\}.$$
  
 $52^{\infty} \{g(x) \leftrightarrow G(\omega) : |G(\omega)| = M(\omega) \text{ for all } \omega\}$ 

where g(x) is the pixel intensity (written one dimensionally for simplicity) and  $G(\omega)$  is the Fourier transform of g(x). The projections  $P_1$  onto  $\xi_1$  and  $P_2$  onto  $\xi_2$  are given by

$$P_{\uparrow g} = \begin{cases} g(x), & x \in \Re \\ \underline{\mathfrak{U}}(x) & \text{otherwise} \end{cases}$$

 $P_{\alpha}g \leftrightarrow M(w)e^{ia(w)}$ 

where o( w) is the phase of G(w).

20

28

94

43

68

88

This process defines the iterations as  $g_{n+1} = 1, 7g_0$ , with  $T_1 = 1+\delta_1(P_1 - 1), i = 1,2$ . However, the relaxation parameters can be set to  $\lambda_1 = \lambda_2 = 1$ , thus reducing the iterations to  $g_{n+1} = P_1 P_2 g_n$ . Additionally, the iteration equation is communited to  $g_{n+1} = P_1 P_2 g_n$ . Such that spatial constraints are applied first, followed by operating constraints. Powels in region  $\mathfrak A$  and  $\mathfrak A$  in the final synthesized region may not be identical to the original pixel values, but the continuity across the edule of the synthesized fregion will be improved in the pixel  $\mathfrak A$  and  $\mathfrak A$  in the final synthesized region will be improved by the synthesized region will be improved by  $\mathfrak A$ .

The iterative process as described with respect to Figure 1 can be summarized as follows for the kith iteration

## 1) Apply spatial domain constraints

$$g'_{K}(x,y) = \begin{cases} g_{K}(x,y) & (x,y) \in \Re \\ \Re(x,y) & \text{otherwise} \end{cases}$$

2) Founer transform q'k(x,v)

 $G(u,v) = FT \{g'_*(x,y)\}.$ 

3) Apply spectral domain constraints

$$\mathfrak{A}(u,v) \approx \text{phase of } G(u,v).$$

$$G'_{k}(u,v)=M(u,v)e^{-i\mathfrak{A}(u,v)}.$$

4) Inverse Fourier transform

10

28

20

36

an

48

$$g_{k+1}(x,y) = FT^{-1}\{G_{k}(u,v)\}.$$

As noted above, appropriate normalization of the image data can significantly improve the quality of the synthesis and reduce the required number of iterations. Normalization is used to remove large scale intensity gradients within local areas of the image, while exture, or fire scale variations, are retained. Normalization is applied to the image region 3 prior to beginning the synthesis iterations, and also to all exemplars E, prior to evaluation of the average modulus with the more representative of the texture and be less effected by low spatial frequency terms.

in the preferred embodiment of the present invention, normalization is realized by the local image area intensity gradient being littled to an N<sup>th</sup> order two-dimensional polynomial. The fitted distribution is then subtracted pixet-by being from the image area 3 to create the normalized image area. The synthesis iterations of the present invention are so applied to the normalized image area. The fitted distribution is added to the result of the synthesis iterations to create the final synthesized image area.

A typical polynomial for the normalization is given by:

$$p(x,y) = c_0 + c_1 x + c_2 y + c_3 x y + c_4 x^2 + c_5 y^2 + c_8 x^2 y^2.$$

Clearly, polynomials of any order are possible. The coefficients of the polynomial fit are determined by:

T=F M<sup>3</sup>(MM<sup>4</sup>)<sup>-1</sup>,  
where T = [
$$c_0 c_1...$$
].  
F = [ $(x_0, y_0)((x_1, y_1)...$ ].

$$\mathbf{M}^{t} = \begin{bmatrix} 1 & x_0 & y_0 & x_0 y_0 & x_2^2 & y_2^2 & x_2^2 y_2^2 \\ 1 & x_1 & y_1 & x_1 y_1 & x_2^2 & y_2^2 & x_2^2 y_2^2 \\ \dots & \dots & \dots & \dots & \dots & \dots & \dots \end{bmatrix}$$

and I(x<sub>0</sub>, y<sub>0</sub>) is the intensity value of image area at location (x<sub>0</sub>, y<sub>0</sub>).

To facilitate a better understanding of the present invention, the following description will describe how the present invention provides a synthesized texture for backfilling.

A rectangular region 5 containing the area to be synthesized is selected. Simust include pixels that are part of the background 5 and pixels of the area to be synthesized 5. The background pixels 5 will be used to apply the apatial domain constraint, in a preferred embodiment, the area 5 is selected by sweeping a rectangle with a mouse, and the orea 5 is identified by ersating pixels using a mouse.

As noted above, the purpose of the present invention is to synthesize areas of the mage with textures agriculture reasonable with respect to surrounding areas. To define reasonable, exemplar regions. E, which have texture similar to that to be tacidified are selected. For the case of removing a ball from a grassy yard, exemplars might be nearby grassy regions. Exemplars are normalized using one of the normalization processes described above. The average Fourier transform mobilis of the normalized exemplars is calculated and used as the spectral othership constraint in the flerative synthesis process. At least one exemplar is required, in a preferred embodiment, exemplars E, are selected by sweeping a rectangle with a mouse. The dismensions of E, may be restricted to those of 3 for computational simplicity.

The synthesis iteration process requires an initial estimate  $g_0(x,y)$  of the synthesized area to begin the iterations. Since normalization results in a zero-mean intensity,  $g_0(x,y)$  is filled with zeros. Thereafter, spatial domain constraints

are applied to estimate  $g_k(x,y)$ , yielding  $g_k(x,y)$ . This is the first of four iterated steps. For each iteration, pixels values g(x,y) from region g(x,y) are copied into the synthesized region. This constraint retains continuity of the known background nikels.

A Fourier transform of  $g_k(x_i)$  is then performed to yield the spectral function  $G_k(u,v)$ , and spectral domain constraints, are applied thereto by copying the precalculated average modulus of the exemplars  $M(\omega)$  into  $G_k(u,v)$ , yielding  $G_k(u,v)$ . Find the constraint forces the synthesized area to maintain the special characteristics of the selected exemptain regions, thus retaining the correct texture. Subsequently, an inverse Fourier transform is performed on  $G_k(u,v)$ , yielding the next estimate of the synthesized area  $g_{k+1}(u,v)$ .

If the quality of the synthesized region is adequate, the lineal synthesized region 3" in added to the normalization polynomial poset-by-timel to the estimate  $g_{n,j}(r^{i,j})$ . If the synthesized region is inadequate, the process is repeated with the inadequate region being used as the initial settings to be within the spatial domain constraints are aboved.

An example of synthesizing texture for backfilling in the image region, utilizing Figures 4-11, will be explained below

As noted above, the preparation of images for printing may often require the removal of unwanted objects or regions in the image. In the example explained below, as illustrated in Figure 4, the present invention will be utilized to process an image 1 of a house 2 being prepared for inclusion into a real estate catalog. As illustrated in Figure 4, the image includes a ball 5 lying in the front yeard of a grassy area 4 with a tree 3 nearby, in this example, it is desirable to remove the ball 5 from the forcit ward and backfill the region occurred by the ball 5 with the appropriate grassy texture.

As discussed above, the present invention initially selects a texture exemplar which will be utilized in synthesizing the backfill image. An example of selecting the texture exemplar is illustrated in Figure 9. As shown in Figure 9, a region 7 is selected as the feature exemplar. (The actual texture exemplar is all illustrated in more detail in Figure 10.) This selected texture exemplar 7 includes grassy texture 4 which is what is to be backfilled into the region being presently occupied by the ball 5.

In the preferred embodiment of the present invention, the exemplar 7 is chosen by dragging a restangle, made by a cursor, over the image to a desired location. Once the rectangle has been established, the user can select the exemplar by either activating a graphic user interface button or hitting a specified key on a keyboard. In the preferred embodiment of the present invention, the chosen exemplar is displayed in an exemplar window, as illustrated in Figure 10, and its modulus is displayed in an exemplar window.

Once the fexture exemplar has been selected, the region of the image containing the area to be synthesized is selected. This selection process is likestated in Figure 5. More specifically, Figure 5 shows the selection region 6 which includes pusiels that are part of the background and pixels that are part of the area to be deleted 5

In the preferred embodiment of the present invention, the selection is identified by dragging a rectangle over the image to a desired location. Once the rectangle 6 has been established at the desired location, the user can implement the selection by either activating a graphic user interface button on screen or activating a predetermined key on a keyboard.

In the preferred embodiment of the present invention, the selected area will be displayed in a selection window as illustrated in Figure 6. More specifically. Figure 6 illustrates the selected area as having the object to be removed 5 and the background area 4 (grassy yard).

Once the selection is placed in the selection window, the pixels associated with the target area or the object to be deleted 12 are erased, as alustrated in Figure 7. In a preferred embodiment of the present invention, the erasing of the target pole areas are identified by click and dragging a cursor, using a mouse, in the selection window so as to erase the target poxel. Figure 8 illustrates the actual object 5 which had been erased from the selection window as illustrated in Figure 7.

As discussed above, the present invention then creates an initial estimate to be used in beginning of the synthesis process. In the preferred embodiment of the present invention, the estimate is displayed in the synthesis window latter appropriate de-normalization). The initial estimate is then processed by applying spatial domain constituints to the estimate, performing a Fourier transform upon the spatially constrained estimate, applying spectral domain constraints upon the spectral function generated by the Fourier transform, and performing an inverse Fourier transform upon the spectral function spectral function generated by the Fourier transform, and performing an inverse Fourier transform upon the spectral functions are found to the spectral function of t

As noted above, the results of the inverse Fourier transform provide the next estimate of the synthesized area. In the ordered emborament of the present invention, the de-normalized next estimate is displayed in the synthesis window so that the user can fully evaluate the synthesized area to be used as the backfill.

If the user believes that the new synthesized region is madequate, in the preferred embodiment of the present invention, the user selects a reterate graphic user interface button or a pracedermined skey on the explorated which see sample of the synthesis process to be repeated. If times before the estimate is radially eye for the user's examination with the new Nth time synthesized region being substituted for the initial estimated synthesized region. N being a whole number equal to or greater than 1.

On the other hand, if the user believes that the synthesized region is adequate, the user may select an implementation graphic user interface button which causes the synthesized selection to be permanently saved in the original

mage as illustrated in Figure 11.

The present invention, although described as a method, can be readily implemented on a general purpose compute, a personal compute, or a decidated or specialized digital image processing device, in the preferred embodiment of the present invention, the synthesis process is carried out on a personal computer which may be connected to a scanner network. File server and/or contret.

In recapitulation, the present invention synthesizes textural regions by applying spatial domain constraints to an estimate of the synthesized region, performing a Fourier transform upon the spatialty constrained estimate, applying spectral domain constraints upon the spectral function, and performing an inverse Fourier transform upon the spectrally specified vehicles to yield a synthesized region which can be utilized as bacidill in an image in which an object has been deleted.

Moreover, this process can be iterative in both the spatial and spectral domains until the quality of the synthesized region is acceptable. By utilizing this synthesis process, the present invention is capable of backfilling an area corresponding to a deleted object with new synthesized texture while minimizing border artifacts between the original background and the synthesized image.

### Claims

20

25

3/2

45

SG

- t. A method for generating a synthesized texture comprising the steps of:
  - (a) selecting a texture exemplar from an image;
  - (b) identifying an area of the image to be backfilled;
  - (c) generating an estimate of the synthesized texture;
  - (d) applying predetermined spatial domain constraints to the estimate;
  - (e) performing a Fourier transform on the spatially constrained estimate,
  - (f) applying predetermined spectral domain constraints on the transformed estimate; and (d) performing inverse Fourier transform upon the spectrally constrained estimate to produce a synthesized
  - texture.
- 2. The method as claimed in claim 1, further comprising the steps of:
  - (h) repeating steps (di-(g) upon the results generated in step (g),
  - (ii) determining if the inverse Fourier transformed estimate is an adequate backfill; and
  - (i) executing said step (h) when said substep (i) determines that the estimate is inadequate.
- 35 3. The method as claimed in claim 1 or 2, wherein said step (b) comprises the substeps of:
  - (b1) selecting a region of the image containing the area to be backfilled, the region including pixels of the area to be deleted and pixels that are part of a background around the area to be deleted; and
  - (b2) erasing the pixels of the area to be deleted.
  - 4. The method as claimed in claim 1, 2 or 3, wherein said step (a) comprises the substeps of:
    - (art) normalizing the selected texture exemplar:
    - (a2) calculating an average Fourier transform modulus of the normalized exemplar; and
    - (a3) using the average Fourier transform modulus as the predetermined spectral domain constraints in said step (f).
  - The method as claimed in claim 3, or any claim dependent thereon, wherein said step (b) further comprises the substacs of:
    - (h3) normalizing gixel values of the pixels representing the background; and
    - (b4) using the normalized pixel values of said substep (b3) as the predetermined spatial domain constraints in said state (d).
- 55 6. A method of backdilling areas of an image with synthesized textures, comprising the method of any of the preceding claims and further comprising the step of:
  - (h) inserting the synthesized texture into the area of the image to be backfilled.


- 7. The method as claimed in claim 6, wherein said step (c) comprises the substeps of:
  - (c1) filling the area of the image to be backfilled with zeros, and
  - (c2) generating an estimate of normalized image data representing the synthesized texture; and
  - said step (g) including the substep of (g1) de-normalizing the inverse Fourier transformed estimate to produce the synthesized texture.
- 8. The method as deimed in claim 6 or 7, further comprising the step of:

s

200

25

- (p) repeating steps (d)-(g) upon the results generated in step (g); said step (g) including the substeps of,
  - (g1) gerermining if the inverse Fourier transformed estimate is an adequate backfill.
  - (g2) executing said step (p) when said substep (g1) determines that the estimate is inadequate, and
- (g5) executing said step (h) when said substep (g1) determines that the estimate is adequate.
- 9. The method as claimed in claim 5, 7 or 8, wherein said step (c) including the substeps of
  - (c1) filling the area of the image to be backfilled with zeros, and
  - (c2) generating an estimate of normalized image data representing the synthesized texture; and
    - said step (g) including the substeps of (g1) denormalizing the inverse Fourier transformed estimate to produce the synthesized texture.
- 10. A programmable image processing apparatus when suitably programmed for carrying out the method of any of the precading claims, the apparatus including a processor, memory, and imput/output circuitry.






FIG. 2



FIG. 3





FIG. 4






FIG. 9




FIG. 10




FIG. 11